

Redi Repair Product Range

PRODUCT
FACT
SHEET

Redi Repair provides a simple, efficient and cost effective solution for a damaged or torn conveyor belt. It delivers a fast curing, high quality bond to the belt surface. The two-part 100% solids polyurethane material also provides excellent abrasion and tear resistance. Our Redi Repair accessories have been developed to assist in safe and efficient application of the product by avoiding air entrapment, improving product mixing consistency, minimising waste and increasing productivity

Application

Suitable for repairs to rubber (fabric and steel cord) and PVC (solid woven) conveyor belts, including repairing tears, spot/punctures, holes, skirt damage, edge damage, splice damage and protecting mechanical fasteners.

Colour:	Red	Hardness:	80 - 85A
Shrinkage:	<1%	Shelf life:	12 months @ 22°C
Working time:	10 to 15 mins @ 24°C	Return belt to service:	4 hr @ 24°C



-  Proven Performance
-  Quality Product
-  Flexibility in Design
-  On-time Delivery

FEATURES	BENEFITS
Fast curing (30 minutes)	= Minimises downtime for maintenance = Increases conveyor availability
Working time of 10-15 minutes	= Increases time for applicators to apply product
High viscosity	= Able to be applied on inclines up to 45 degrees without sagging or slumping
High quality bond	= Increases longevity of the repair over traditional techniques
Excellent abrasion and tear resistance	= Increases life in high wear zones = Increases strength throughout the repair
Light and compact	= Reduces hazards associated with manual handling of capital equipment such as vulcanisers and spot presses
Self-mixing	= Product is automatically mixed to correct ratio via self-mixing nozzle eliminating human error = No-hand mixing required
Cost efficient	= Minimal labour to apply = No hire charge for equipment = Long lasting

Redi Repair Product Range

PRODUCT
FACT
SHEET



Repair Materials

Item Code	Description	Unit	Weight		Volume	
			(g)	(oz)	(ml)	(Fl oz)
60-13-100	Redi Repair Natural 85 kit (including 1 x Redi Repair Natural 85, Cleaning Solution N85, Primer N85, mixing nozzle, paint brush, plastic scraper, rubber gloves).	Each	1100	39	1000	34

Accessories

Item Code	Description	Unit	Weight	
			(kg)	(lbs)
60-13-170	Pneumatic caulking gun	Each	1.5	3.0
60-13-171	Manual caulking gun	Each	0.6	1.0
60-13-172	Static mixing nozzle	Each	0.1	0.2
60-13-173	Steel scraper	Each	0.1	0.2
60-13-174	Plastic scraper	Each	0.1	0.2
60-13-175	Paint Brush	Each	0.1	0.2



DISTRIBUTED BY

TSGlobal®

Leaders in Conveyor Products

PO Box 103, HRMC NSW 2300
8 Laurio Place, Mayfield NSW 2304

PHONE +61 2 4968 8500

EMAIL sales@tsglobal.net.au

WEB www.tsglobal.net.au

ABN 30 603 644 748