

R Tungsten Belt Cleaner

PRODUCT
FACT
SHEET

The range of TS Global belt cleaners are guaranteed to reduce carry-back, safety hazards and environmental impact along the conveyor. While it can be used as an individual belt cleaner, best results are achieved when it is part of a complete cleaning system. Working in conjunction with a primary cleaner, the R belt cleaner removes the fine residue left behind by the primary cleaner. You can choose to install the R belt cleaner with or without water sprays – either way the results are impressive. Balancing cost effectiveness with long life functionality makes this the ideal choice for your application.

Application

Installed at the head end or discharge point of any conveyor belt.

Suitable to single or bi-directional conveyors.

Suitable for use on vulcanised conveyor belts only.



-  Proven Performance
-  Quality Product
-  Flexibility in Design
-  On-time Delivery

FEATURES	BENEFITS
Performs final cleaning ensuring up to 98% of fines are removed	= Fines returned to the product flow, maximising revenue
Manufactured from high grade stainless steel	= Increases longevity in structural components
Manufactured in either standard, heavy duty or super pole configuration	= Allows the duty of the cleaner to be matched to the size and speed of the conveyor
Supplied with bolt-on tungsten tips	= Allows alignment of cleaning elements to deliver optimum performance
	= Increases life expectancy of tungsten tip
	= Minimises maintenance costs
Choice of high grade tungsten tip thickness	= Increases life expectancy of tungsten tip
	= Minimises maintenance costs
	= Optimises performance
Our components are interchangeable with most brands	= Cost savings achieved without the need to replace the cleaner
Supplied with unique two piece clamping system	= Allows the pole to be supported while removing cleaner
Our components are manufactured from castings with smooth rounded edges	= Ensures uniformity of product
	= Consistent accuracy of product improves serviceability
	= Reduces exposure to potential hand injuries

R Tungsten Belt Cleaner

PRODUCT
FACT
SHEET



Item Code	Description	Unit	Pole Length		Pole Diameter		Belt Width		Number of Blades	Weight	
			(mm)	(inches)	(mm)	(inches)	(mm)	(inches)		(kg)	(lbs)
15-10-001	Cleaner R 0450 Tungsten	Each	1250	49 3/16	48	1 7/8	400	18	3	19	42
15-10-002	Cleaner R 0600 Tungsten	Each	1350	53 1/8	48	1 7/8	600	24	4	21	46
15-10-003	Cleaner R 0750 Tungsten	Each	1500	59 1/16	48	1 7/8	750	30	5	23	51
15-10-004	Cleaner R 0900 Tungsten	Each	1650	64 15/16	60	2 3/8	900	36	6	28	62
15-10-005	Cleaner R 1050 Tungsten	Each	1800	70 7/8	60	2 3/8	1050	42	7	29	64
15-10-006	Cleaner R 1200 Tungsten	Each	1950	76 3/4	73	2 7/8	1200	48	8	41	90
15-10-007	Cleaner R 1400 Tungsten	Each	2200	86 5/8	73	2 7/8	1400	56	9	45	99
15-10-008	Cleaner R 1500 Tungsten	Each	2350	92 1/2	73	2 7/8	1500	60	10	47	104
15-10-009	Cleaner R 1600 Tungsten	Each	2500	98 7/16	73	2 7/8	1600	64	10	48	106
15-10-010	Cleaner R 1800 Tungsten	Each	2650	104 5/16	73	2 7/8	1800	72	12	53.2	117
15-11-001	Cleaner R 1050 Tungsten Reinforced Pole	Each	1800	70 7/8	60	2 3/8	1050	42	7	37	82
15-11-002	Cleaner R 1200 Tungsten Reinforced Pole	Each	1950	76 3/4	73	2 7/8	1200	48	8	49	108
15-11-003	Cleaner R 1400 Tungsten Reinforced Pole	Each	2200	86 5/8	73	2 7/8	1400	56	9	54	119
15-11-004	Cleaner R 1500 Tungsten Reinforced Pole	Each	2350	92 1/2	73	2 7/8	1500	60	10	57	126
15-11-005	Cleaner R 1600 Tungsten Reinforced Pole	Each	2500	98 7/16	73	2 7/8	1600	64	10	58	128
15-11-006	Cleaner R 1800 Tungsten Reinforced Pole	Each	2650	104 5/16	73	2 7/8	1800	72	12	65	143
15-11-007	Cleaner R 2000 Tungsten Reinforced Pole	Each	2950	116 1/8	73	2 7/8	2000	80	13	70	154
15-11-008	Cleaner R 2200 Tungsten Reinforced Pole	Each	3100	122 1/16	73	2 7/8	2200	86	14	75	165
15-11-009	Cleaner R 2500 Tungsten Reinforced Pole	Each	3400	133 3/8	73	2 7/8	2500	98	16	83	183

DISTRIBUTED BY

TSGlobal[®]
Leaders in Conveyor Products

PO Box 103, HRMC NSW 2300
8 Laurio Place, Mayfield NSW 2304

PHONE +61 2 4968 8500
EMAIL sales@tsglobal.net.au
WEB www.tsglobal.net.au

ABN 30 603 644 748